



DIGITAL DUST MONITOR FOR CONTINUOUS OUTDOOR MONITORING OF PARTICLES IN AIR

INFRA X20DM2 Dust monitor

The INFRA system is used to monitor construction, activities, rock blasting, train traffic, road traffic, vibration in buildings etc.

During excavation, crushing and demolition dust particles occur which are detrimental to health. Operation of trains, subways, buses, trucks and other vehicles will also give rise to harmful particles.

The INFRA X20DM2 Dust Monitor is a complete sensor for continuous monitoring of particulates in the air. It can be directly connected to Sigicom's INFRA-measuring system with ready-made solutions for data communications, database on the internet and web presentation of measurement data.

- Measuring range: PM10 and TSP: 0.01–6000 $\mu\text{g}/\text{m}^3$
PM2.5 and PM1.0: 0.001–600 $\mu\text{g}/\text{m}^3$
- Measures and adjusts for temperature- and humidity-variations


The measurement is based on a very well established and safe technology. It has a built-in pump that draws in air to a calibrated laser based refraction detector.

Output is digital and is transmitted directly to a connected INFRA Mini/Master/Micro. This provides a continuous measurement with the opportunity to identify the level of particle concentration.

In the INFRA system it is possible to trigger an alarm light, to send SMS or e-mail when the particle level is above a preset level.



- **Measures simultaneously the concentration of particles PM1.0, PM2.5 PM10 and TSP**
- **Measuring range PM1.0 & PM2.5: 0.001-600 $\mu\text{g}/\text{m}^3$ PM10 & TSP: 0.01-6000 $\mu\text{g}/\text{m}^3$**
- **Alarm level on PM10 concentration: 5-5000 $\mu\text{g}/\text{m}^3$**





Technical Data

PARTICLE SIZE

Measures simultaneously PM1.0, PM2.5, PM10 and TSP
(total suspended particles)

RESOLUTION

0.01 µg/m³

INTERVAL TIME

1–60 minutes

ACCURACY

+/-5% of reading traceable to SAE Fine test dust

FLOW RATE RANGE

600 ml /min

INTERNAL BATTERY RUN TIME

>10 hours when heating is disabled

EXTERNAL POWER

100–240V AC 50-60 Hz power supply
Heating 12W

DIMENSIONS

370 x 320 x 180 mm (HxWxD)
(14 x 12 x 6 in)

OPERATING ENVIRONMENT

-5 °C to +40 °C (23 to 104 °F), 10-95 RH, noncondensing

MAINTENANCE

Flow and filter check.
Minor maintenance needed every 3rd month

WEIGHT

10 kg (22 lbs)